Chicago Adhesive Products Company

4658 West 60th Street, Chicago, Illinois 60629

Telephone: (312) 581-1300

**** MATERIAL SAFETY DATA SHEET ****

Emergency Phone #: 1-800-424-9300 Information Phone#: (312)-581-1300 MAY 04 1994

Latest Revision Date...02/18/93

Print Date.....02/18/93

CHAPCO 400 COVE BASE ADHESIVE

SECTION 1 HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HMIS...... 0 = MINIMAL; 1 = SLIGHT; 2 = MODERATE; 3 = SERIOUS; 4 = SEVERE

PERSONAL PROTECTION...:B; GLOVES, GOGGLES

SECTION 2 PRODUCT IDENTIFICATION

MANUFACTURER'S NAME..... CHICAGO ADHESIVE PRODUCTS CO.

PRODUCT NAME OR NUMBER..... 400

TRADE NAME OR CHEMICAL NAME... CHAPCO 400 COVE BASE ADHESIVE

SECTION 3 HAZARDOUS INGREDIENTS / IDENTITY INFORMATION						
CHEMICAL NAME(S)	CAS NUMBER	% WT	ACGIH-TWA	TLV-STEL	PEL	SEC.313
ETHYLENE GLYCOL	107-21-1	2.0	50 PPM	N/A	50 PPM	Yes
VM&P	64742-89-8	3.0	300 PPM	400 PPM	300 PPM	No
NON-HAZARDOUS CHEMICALS						No
FILLER CLAY		52.0	N/A	N/A	N/A	No
LATEX POLYMER	N/A	20.0	N/A	N/A	N/A	No
HYDROCARBON RESIN	N/A	12.0	N/A	N/A	N/A	No
WATER	7732-18-5	6.0	N/A	N/A	N/A	No
EMULSIFIERS	N/A	3.0	N/A	N/A	N/A	No
MINERAL SPIRITS	64742-88-7	2.0	100 PPM	N/A	N/A	No

SECTION 4 PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING/MELTING POINT @760 mm Hg... 212 DEGREES F.

рн..... 8.9 - 9.4

VAPOR PRESSURE mm Hg @20° C..... N/A

VAPOR DENSITY (Air = 1)........... N/A

PERCENT VOLATILE BY WEIGHT (%)..... N/A

SPECIFIC GRAVITY OR BULK DENSITY... 1.47

SOLUBILITY IN WATER..... DISPERSIBLE WHILE STILL WET

EVAPORATION RATE (Buac = 1)..... N/A

APPEARANCE/ODOR...... OFF-WHITE PASTE; MILD SWEET ODOR

SECTION 5 FIRE AND EXPLOSION HAZARD DATA

FLASH POINT °F (Test Method)..... NON-FLAMMABLE

FLAMMABLE LIMITS:

EXTINGUISHING MEDIA..... WILL NOT SUPPORT COMBUSTION

SPECIAL FIRE FIGHTING PROCEDURES... N/A

UNUSUAL FIRE & EXPLOSION HAZARDS... PRODUCT WILL NOT BURN BUT MAY SPATTER IF TEPERATURE EXCEEDS BOILING POINT.

SECTION 6 REACTIVITY DATA

PRODUCT STABILITY...... STABLE
Conditions to Avoid..... NONE KNOWN
CHEMICAL INCOMPATIBILITY..... OXIDIZING AGENTS

CHAPCO 400 COVE BASE ADHESIVE

REACTIVITY DATA CONT'D SECTION 6 HAZARDOUS DECOMPOSITION PRODUCTS... OXIDES OF CARON IF CO-BURNED WITH FLAMMABLE MATERIALS. HAZARDOUS POLYMERIZATION..... WILL NOT OCCUR Conditions to Avoid...... NONE KNOWN SECTION 7 HEALTH HAZARD DATA * EFFECTS OF OVEREXPOSURE ROUTES OF ENTRY:..... INHALATION, INGESTION AND DIRECT DERMAL EXPOSURE. IRRITATION OF THE MUCOUS MEMBRANES OF THE NOSE, THROAT, RESPIRATORY TRACT AND SYMPTOMS OF HEADACHE AND NAUSEA. CARCINOGENICITY...... NO KNOWN EFFECTS SIGNS AND SYMPTOMS OF EXPOSURE.... NONE EXPECTED BUT EXCESSIVE INHALATION MAY CAUSE NAUSEA AND DIZZINESS. ACUTE EFFECTS OF OVEREXPOSURE..... HEADACHES, DIZZINESS, EYE, NOSE, THROAT AND LUNG DISTRESS FROM VAPORS. EYE CONTACT CAN CAUSE SEVERE EYE IRRITATION, REDNESS, TEARING, BLURRED VISION; CAN CAUSE RESPIRATORY IRRITATION AND GASTRIC DISTURBANCE. CHRONIC EFFECTS OF OVEREXPOSURE... PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE IRRITATION AND INFLAMMATION. EMERGENCY/FIRST AID PROCEDURES.... SEVERE OVEREXPOSURE: REMOVE TO FRESH AIR. ADMINISTER ARTIFICIAL RESPIRATION OR OXYGEN. CALL PHYSICIAN IMMEDIATELY. EYES: FLUSH WITH WATER FOR FIFTEEN (15) MINUTES, LIFTING EYELIDS OCCASIONALLY. GET IMMEDIATE ATTENTION. SKIN: WASH WITH SOAP AND WATER. IF IRRITATION DEVELOPS OR PERSISTS, SEE PHYSICIAN IMMEDIATELY. INHALATION: SHOULD INHALATION PROBLEMS OCCUR, MOVE VICTIM TO FRESH AIR. AID IN BREATHING, IF NECESSARY, GET IMMEDIATE MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY. CONTROL MEASURES SECTION 8 RESPIRATORY PROTECTION...... NONE REQUIRED IF GOOD VENTILATION IS MAINTAINED. VENTILATION..... LOCAL EXHAUST; USE WITH ADEQUATE VENTILATION. OPEN DOORS AND WINDOWS. UTILIZE OTHER MEANS TO ENSURE FRESH AIR ENTRY AND EXHAUST. PROTECTIVE CLOTHING/GLOVES... IMPERVIOUS GLOVES EYE PROTECTION...... SAFETY GOGGLES RECOMMENDED OTHER PRECAUTIONS...... N/A WORK/HYGIENIC PRACTICES..... AVOID PROLONGED OR REPEATED SKIN CONTACT, OR WEAR IMPERVIOUS PROTECTIVE CLOTHING. THOROUGH WASHING OF SKIN AFTER WORK AND BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. WASH CLOTHING AFTER USE SECTION 9 PRECAUTIONS FOR SAFE HANDLING AND USE SPILL OR LEAK PROCEDURES..... SCRAPE UP AND PLACE IN A CLOSED CONTAINER. HAZARDOUS SUBSTANCE SUPERFUND.... N/A WASTE DISPOSAL METHOD...... MATERIAL SHOULD BE LAND FILLED ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS. HAZARDOUS WASTE 40CFR261..... N/A PRECAUTIONS IN HANDLING/STORING... KEEP CONTAINER CLOSED AND STORE IN COOL PLACE. USE WITH ADEQUATE VENTILATION. OTHER PRECAUTIONS..... SUPPLY SUFFICIENT VENTILATION. SHIPPING DATA SECTION 10 D.O.T. PROPER SHIPPING NAME..... ADHESIVES HAZARDOUS SUBSTANCE 49CFR CERCLA... N/A D.O.T. HAZARD CLASS..... N/A D.O.T. LABELS REQUIRED..... N/A D.O.T. PLACARDS REQUIRED..... N/A BILL OF LADING DESCRIPTION..... ADHESIVES CC NO..... N/A

CHRPCO

SECTION 7

Chicago Adhesive Products Company

4658 West 60th Street, Chicago, Illinois 60629

Telephone: (312) 581-1300

```
**** MATERIAL SAFETY DATA SHEET ****
Emergency Phone #: 1-800-424-9300
Information Phone#: (312)-581-1300
                                                                                                        CHAPCO 750 CLEAR LATEX VCT ADHESIVE
Latest Revision Date...07/20/92
Print Date.....07/20/92
                                               HAZARDOUS MATERIAL IDENTIFICATION SYSTEM
SECTION 1
 HMIS...... 0 = MINIMAL; 1 = SLIGHT; 2 = MODERATE; 3 = SERIOUS; 4 = SEVERE
 HEALTH HAZARD.....:1
 REACTIVITY.....: 10
 PERSONAL PROTECTION... :B; GLOVES AND GOGGLES
    make hand? State I make global states states
                                                                       PRODUCT IDENTIFICATION
SECTION 2
 MANUFACTURER'S NAME..... CHICAGO ADHESIVE PRODUCTS CO.
 PRODUCT NAME OR NUMBER..... 750
 TRADE NAME OR CHEMICAL NAME... CHAPCO 750 CLEAR LATEX VCT ADHESIVE
                                          HAZARDOUS INGREDIENTS / IDENTITY INFORMATION
SECTION 3
                                                                                                                                                                                        SEC.313
                                                                                % WT
                                                                                                 ACGIH-TWA
                                                                                                                               TLV-STEL
                                                                                                                                                           PEL
                                                          CAS NUMBER
CHEMICAL NAME(S)
                                                                                                                                                                                        No
                                                                                                                                                           300 PPM
                                                                                                  300 PPM
                                                                                                                               400 PPM
                                                            64742-89-8
                                                                                7.3
VM&P
                                                                                                                               N/A
                                                                                                                                                           50 PPM
                                                                                                                                                                                        Yes
                                                                                                  50 PPM
                                                               107-21-1
                                                                              1.5
ETHYLENE GLYCOL
                                                       PHYSICAL/CHEMICAL CHARACTERISTICS
SECTION 4
 BOILING/MELTING POINT @760 mm Hg... 212 DEGREES F.
 pH...... 8.5 TO 9.5
 VAPOR PRESSURE mm Hq @20° C..... N/A
 VAPOR DENSITY (Air = 1)........... N/A
 PERCENT VOLATILE BY WEIGHT (%).... N/A
 SPECIFIC GRAVITY OR BULK DENSITY... 1.07
 SOLUBILITY IN WATER..... DISPERSIBLE WHILE STILL WET
 EVAPORATION RATE (Buac = 1)..... N/A
 APPEARANCE/ODOR...... BUFF COLOR - SWEET ODOR
 FIRE AND EXPLOSION HAZARD DATA
 SECTION 5
 FLASH POINT 'F (Test Method)..... NON-FLAMMABLE
 FLAMMABLE LIMITS:..... N/A
 LEL..... N/A
 UEL..... N/A
 EXTINGUISHING MEDIA..... WILL NOT SUPPORT COMBUSTION
 SPECIAL FIRE FIGHTING PROCEDURES... NONE KNOWN
 UNUSUAL FIRE & EXPLOSION HAZARDS... PRODUCT WILL NOT BURN BUT MAY SPATTER IF TEMPERATURE EXCEEDS BOILING POINT.
 The same was the companies and make the same who the same gave the same the same time and the companies and the same time.
                                                                               REACTIVITY DATA
 SECTION 6
 PRODUCT STABILITY..... STABLE
    Conditions to Avoid..... NONE KNOWN
 CHEMICAL INCOMPATIBILITY..... OXIDIZING AGENTS
 HAZARDOUS DECOMPOSITION PRODUCTS... THERMAL DECOMPOSITION MAY FORM CARBON MONOXIDE
 HAZARDOUS POLYMERIZATION..... WILL NOT OCCUR
    Conditions to Avoid...... NONE KNOWN
```

HEALTH HAZARD DATA * EFFECTS OF OVEREXPOSURE

IRRITATION OF THE MUCOUS MEMBRANES OF THE NOSE, THROAT, RESPIRATORY TRACT AND SYMPTOMS OF

HEALTH HAZARDS...... INHALATION: ADVERSE HEALTH EFFECTS FROM VAPORS IN POORLY VENTILATED AREAS; MAY INCLUDE

ROUTES OF ENTRY:..... INHALATION, INGESTION AND DIRECT DERMAL EXPOSURE.

HEYDYCHE YND NYHCEY

CHAPCO 750 CLEAR LATEX VCT ADHESIVE

CHAPCO /50 CLEAR LATEX VCT ADRESIVE
SECTION 7 HEALTH HAZARD DATA * EFFECTS OF OVEREXPOSURE CONT'D CARCINOGENICITY
CONTROL MEASURES RESPIRATORY PROTECTION
SECTION 9 PRECAUTIONS FOR SAFE HANDLING AND USE SPILL OR LEAK PROCEDURES SCRAPE UP EXCESS. CLEAN WITH SOAPY WATER. HAZARDOUS SUBSTANCE SUPERFUND N/A WASTE DISPOSAL METHOD INCINERATE UNDER SAFE CONDITIONS OR IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. HAZARDOUS WASTE 40CFR261 N/A PRECAUTIONS IN HANDLING/STORING STORE IN ORIGINAL SEALED CONTAINERS AT TEMPERATURE NOT OVER 100 DEGREES F. OTHER PRECAUTIONS SUPPLY SUFFICIENT VENTILATION.
SECTION 10 D.O.T. PROPER SHIPPING NAME ADHESIVES HAZARDOUS SUBSTANCE 49CFR CERCLA N/A HAZARD CODE N/A D.O.T. HAZARD CLASS N/A D.O.T. LABELS REQUIRED N/A D.O.T. PLACARDS REQUIRED N/A POISON CONSTITUENT N/A BILL OF LADING DESCRIPTION ADHESIVES CC NO N/A UN/NA CODE UN-1133 CHEMICAL EMERGENCY CHEMTREC 24 HOUR: 1-800-424-9300