# **Material Safety Data Sheet**



1310 Seaboard Industrial Blvd Atlanta, GA 30318 1-877-793-7776

Section 1. Chemical Product and Company Identification

LEMON FURNITURE POLISH

0

**Product use** 

Furniture Polish & Cleaner

Product code

**R044** 

Date of issue

08/05/08

Supersedes

#### **Emergency Telephone Numbers**

For MSDS Information:

Compliance Services 1-877-793-7776

For Medical Emergency

INFOTRAC: (877) 541-2016 Toll Free - All Calls

For Transportation Emergency

CHEMTREC: (800) 424-9300 - All Calls Recorded In the District of Columbia (202) 483-7616

Prepared By

**Compliance Services** 1420 Seaboard Industrial Blvd. Atlanta, GA 30318

## Section 2. Hazards Identification

**Emergency overview** 

WARNING

"Hazard Determination System (HDS): Health, Flammability, Reactivity 1

CAUSES EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

CONTENTS UNDER PRESSURE.

NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

## Acute Effects

Routes of Entry

Dermal contact. Inhalation.

Eyes Skin

Causes eye irritation. Inflammation of the eye is characterized by redness, watering and itching. May cause skin irritation. Skin inflammation is characterized by itching, scaling, or reddening.

Inhalation Avoid breathing vapors, spray or mists. Over-exposure by inhalation may cause respiratory irritation. Inhalation of spray mists or vapors may cause central nervous system depression

characterized by headache, dizziness, nausea, and/or stupor.

Ingestion

May be harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause

**Chronic effects** 

Prolonged or repeated contact may dry skin and cause irritation.

Carcinogenicity Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

Additional Information: See Toxicological Information (Section 11)

## Section 3. Composition/Information on Ingredients

Name of Hazardous Ingredients	CAS number	% by Weight
ISOPARAFFINIC SOLVENT; hydrotreated light distillate (petroleum)	64741-73-7	10 - 20
HYDROCARBON PROPELLANT; blend of propane & isobutane	75-28-5, 74-98-6	10 - 20
MINERAL OIL; petrolatum; mineral oil, white.	8042-47-5	5 - 15

### Section 4. First Aid Measures

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and Eye Contact

remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.

Skin Contact Flush contaminated skin with plenty of water. Get medical attention if irritation develops.

Inhalation Move exposed person to fresh air. If irritation persists, get medical attention.

Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be Ingestion

kept low so that vomit does not enter the lungs. If affected person is conscious, give plenty of water to drink.

Never give anything by mouth to an unconscious person. Get medical attention immediately.

Product code R044

**Material Safety Data Sheet** 

Product Name LEMON FURNITURE POLISH

Section 5. Fire Fighting Measures

Not available.

Flammable Limits Not available.

Flammability Non-flammable. (CSMA Method)

Fire hazard CONTENTS UNDER PRESSURE. In a fire or if heated, a pressure increase will occur and

the container may burst, with the risk of a subsequent explosion. Bursting aerosol containers

National Fire Protection Association (U.S.A.)

may be propelled from a fire at high speed.

Fire-Fighting **Procedures** 

Flash Point

Use an extinguishing agent suitable for the surrounding fire, Cool closed containers exposed to

fire with water. Fire-fighters should wear appropriate protective equipment.

#### Section 6. Accidental Release Measures

Spill Clean up Large spills are unlikely due to packaging.

## Section 7. Handling and Storage

Put on appropriate personal protective equipment (see section 8). Store and use away from heat, sparks, open flame Handling

or any other ignition source. Avoid contact with eyes, skin and clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Observe label precautions. Wash thoroughly after handling.

CONTENTS UNDER PRESSURE. Do not puncture, incincrate or store the container at temperatures above 49°C Storage

(120°F) or in direct sunlight. Keep out of the reach of children.

#### Section 8. Exposure Controls/Personal Protection

#### Product name

HYDROCARBON PROPELLANT; blend of propane & isobutane

ISOPARAFFINIC SOLVENT; hydrotreated light distillate

ISOPARAFFINIC SOLVENT; petroleum naphtha, light alkylate

## Exposure limits

ACGIII TLV / OSHA PEL (United States). Notes: Propane

TWA: 1000 ppm 8 hour(s). NIOSH REL (United States).

TWA: 1200 mg/m3 Form: Vapor

Supplier Suggested TLV (United States). TWA: 1400 mg/m3 8 hour(s).

#### Personal Protective Equipment (PPE)

Eyes

Safety glasses:

Body

For prolonged or repeated handling, use the following type of

gloves: Neoprene gloves. Nitrile gloves. Rubber gloves.

Respiratory Use with adequate ventilation.

## Section 9. Physical and Chemical Properties

**Physical State** 

Liquid. [Aerosol.] Not applicable

**Boiling Point** 

Hq

104,44°C (220°F)

Specific Gravity

Solubility

Insoluble in the following materials: cold water and

hot water.

Color Opaque. Emulsion. Odor Pleasant. Lemon-like.

Vapor Pressure Not determined.

Vapor Density Not determined. Evaporation Rate 1 (Water = 1)

DO

VOC (Consumer) 158 (g/l). 1.3 lbs/gal (17.0%)

## Section 10. Stability and Reactivity

Stability and Reactivity

The product is stable.

Incompatibility

Keep away from heat, sparks and flame. Reactive or incompatible with the following materials:

oxidizing materials and acids.

**Hazardous Polymerization** 

Will not occur.

Hazardous Decomposition Products carbon oxides (CO, CO<sub>1</sub>)

## Section 11. Toxicological Information

**Acute Toxicity** 

Product/ingredient name

Result

LD50 Oral

Species Rabbit

Dose

Exposure

(petroleum)

Isoparaffinic Solvent, Hydrotreated light distillate

LD50 Denna

Rai

>2000 mg/kg >2000 mg/kg

Product code R044	duct code R044 Material Safety		ata Sheet	Product I	Product Name LEMON FURNITURE POLISH		
Section 12. Ecologic	cal Information		1				
Environmental Effec	ts No kno	own significant effects or c	ritical hazards	i.			
Not available							
Section 13. Disposa	l Consideration	ns					
Waste Information Waste must be disposed regional authorities for a  Waste Stream Non-l	dditional informa	with federal, state and location.	al environmen	tal control regu	ulations. Consul	t your local or	
Section 14. Transpo	rt Information						
Regulatory information	UN number	Proper shipping name	Classes	PG*	Label		
DOT Classification	Not regulated.	Consumer commodity ORM-D					
IMDG Class	Not determined.						
OTE: DOT classification ne Bill of Lading with your G*: Packing group	applies to most par shipment.	ckage sizes. For specific co	ntainer size cla	assifications or	for size exception	ns, refer to	
Section 15. Regulate	ory Information			Vii		10	
U.S. Federal Regulati SARA 313 toxic chen No products were found.		and release reporting:		73			
	WA) 311: No pro ) 112 regulated t						
State Regulations				· · ·			

California Prop 65

No products were found.

## Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution.

Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

\*NOTE Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910 1200, the preparer may choose to provide them. HDS ratings are in the used with a fully implemented program to relay the meanings of this scale.