



# Material Safety Data Sheet

Document Code: Polycrylic/MW

Date of Preparation

Version: 03

March 14, 2003

## Section 1 - Product and Company Identification

### PRODUCT NAME & NUMBERS

**MINWAX® POLYCRYLIC® Protective Finish**

3333 Satin Rockler SKUs:  
 4444 Semi-Gloss 31895, 32135, 33821, 34701, 35455, 39863  
 5555 Gloss

### HMS CODES

Health 2  
 Flammability 0  
 Reactivity 0

### MANUFACTURER'S NAME

MINWAX Company  
 10 Mountainview Road  
 Upper Saddle River, NJ 07458

### EMERGENCY TELEPHONE NO.

(216) 566-2917

### INFORMATION TELEPHONE NO.

(800) 523-9299

## Section 2 - Composition/Information on Ingredients

% WT.	CAS No.	Ingredient Name	Vapor Pressure
1	34590-94-8	<b>2-Methoxymethylethoxypropanol</b> ACGIH TLV 100 ppm (skin) ACGIH TLV 150 ppm (skin) STEL OSHA PEL 100 ppm (skin) OSHA PEL 150 ppm (skin) STEL	0.4 mm
2	29911-28-2	<b>1-(2-Butoxymethylethoxy)-propanol</b> ACGIH TLV Not Available OSHA PEL Not Available	0.06 mm
4	5131-66-8	<b>Butoxypropanol</b> ACGIH TLV Not Available OSHA PEL Not Available	0.6 mm
3	107-21-1	<b>Ethylene Glycol</b> ACGIH TLV 50 ppm CEILING OSHA PEL 50 ppm CEILING	0.12 mm
1	9014-85-1	<b>Decylpoly(ethyleneoxy)ethanol</b> ACGIH TLV Not Available OSHA PEL Not Available	
2	872-50-4	<b>1-Methyl-2-Pyrrolidone</b> ACGIH TLV Not Available OSHA PEL Not Available	1 mm

## Section 3 - Hazards Identification

### ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

### EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and upper respiratory system. In a confined area vapors in high concentration may cause headache, nausea or dizziness.

### SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE - None generally recognized.

### CANCER INFORMATION

For Complete Discussion of Toxicology Data Refer to Section 11.

- Continued -

RTD200000211AA

## Section 4 – First Aid Measures

- If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.
- If on SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.
- If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.
- If SWALLOWED: Do not induce vomiting. Get medical attention immediately.

## Section 5 – Fire Fighting Measures

FLASH POINT	LEL	UEL
>200 °F PMCC	N.A.	N.A.

FLAMMABILITY CLASSIFICATION - Not Applicable

EXTINGUISHING MEDIA - Carbon Dioxide, Dry Chemical, Alcohol Foam

### UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

### SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

## Section 6 – Accidental Release Measures

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area. Remove with inert absorbent.

## Section 7 – Handling and Storage

STORAGE CATEGORY - DOL Storage Class IIIB

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

## Section 8 – Exposure Controls/Personal Protection

### PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid contact with skin and eyes. Avoid breathing vapor and spray mist. Wash hands after using.

These coatings may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m<sup>3</sup> (total dust), 3 mg./m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg./m<sup>3</sup> (total dust), 5 mg./m<sup>3</sup> (respirable fraction).

Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

**Section 8 – Exposure Controls/Personal Protection (continued)**

## VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

## RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

## PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

## EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

**Section 9 – Physical and Chemical Properties**

PRODUCT WEIGHT	8.51-8.55 lb/gal	EVAPORATION RATE	Slower than Ether
SPECIFIC GRAVITY	1.02-1.03	VAPOR DENSITY	Heavier than Air
BOILING POINT	212-449 °F	MELTING POINT	Not Available
VOLATILE VOLUME	71 %	SOLUBILITY IN WATER	Not Available
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)			
	2.5 lb/gal	Less Federally Exempt Solvents	
	1.0-1.1 lb/gal	Emitted VOC	

**Section 10 – Stability and Reactivity**

STABILITY - Stable

CONDITIONS TO AVOID - None known.

INCOMPATIBILITY - None known.

HAZARDOUS DECOMPOSITION PRODUCTS - By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION - Will not occur

**Section 11 – Toxicological Information**

## CHRONIC HEALTH HAZARDS

No ingredient in these products is an IARC, NTP or OSHA listed carcinogen.

Ethylene Glycol is considered an animal teratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver and urinary systems.

## TOXICOLOGY DATA

CAS No.	Ingredient Name			
34590-94-8	<b>2-Methoxymethylethoxypropanol</b>	LC50	RAT	4HR Not Available
		LD50	RAT	5135 mg/kg
29911-28-2	<b>1-(2-Butoxymethylethoxy)-propanol</b>	LC50	RAT	4HR Not Available
		LD50	RAT	Not Available
5131-66-8	<b>Butoxypropanol</b>	LC50	RAT	4HR Not Available
		LD50	RAT	1900 mg/kg

## TOXICOLOGY DATA (continued)

CAS No.	Ingredient Name				
107-21-1	Ethylene Glycol	LC50	RAT	4HR	Not Available
		LD50	RAT		4700 mg/kg
9014-85-1	Decylpoly(ethyleneoxy)ethanol	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
872-50-4	1-Methyl-2-Pyrrolidone	LC50	RAT	4HR	Not Available
		LD50	RAT		4200 mg/kg

**Section 12 – Ecological Information**

ECOTOXICOLOGICAL INFORMATION - No data available.

**Section 13 – Disposal Considerations**

## WASTE DISPOSAL METHOD

Waste from these products is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

**Section 14 – Transport Information - No data available.****Section 15 – Regulatory Information**

## SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
107-21-1	Ethylene Glycol	3	
872-50-4	1-Methyl-2-Pyrrolidone	2	

## CALIFORNIA PROPOSITION 65

WARNING: These products contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

## TSCA CERTIFICATION

All chemicals in these products are listed, or are exempt from listing, on the TSCA Inventory.

**Section 16 – Other Information**

CANADIAN DISTRIBUTOR: *Consumer Brands Canada Inc.*  
 200 Confederation Parkway  
 Vaughn, ON L4K 4T8

NOTE: These products have been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

The above information pertains to these products as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to these products may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.